CSE 167:

Introduction to Computer Graphics Lecture #14: Toon Shading


> Jürgen P. Schulze, Ph.D. University of California, San Diego Fall Quarter 2016

Announcements



Toon Shading


- A.k.a. Cel Shading ("Cel" is short for "celluloid" sheets, on which animation was hand-drawn)
- Gives any 3D model a cartoon-style look
- Emphasizes silhouettes
- Discrete steps for diffuse shading, highlights
- Non-photorealistic rendering method (NPR)
- Programmable shaders allow real-time performance



plastic shader

toon shader

Source: Wikipedia










Approach

- Start with regular 3D model
- Apply two rendering tricks:
 - Silhouette edges
 - ▶ Emphasize pixels with normals perpendicular to viewing direction.
 - Discretized shading
 - Conventional (smooth) lighting values calculated for each pixel, then mapped to a small number of discrete shades.



Source: Wikipedia




Silhouette Edges

- Silhouette edge detection
 - Compute dot product of viewing direction v and normal n

$$edge = \max(0, \mathbf{n} \cdot \mathbf{v})$$





Use ID texture to define edge ramp for smoother transition uniform sample1D edgeramp;
 e = texture1D(edgeramp,edge);





edge


Discretized Shading

- Compute diffuse and specular shading diffuse = $\mathbf{n} \cdot \mathbf{L}$ specular = $(\mathbf{n} \cdot \mathbf{h})^s$
- Discretize shading
- Approaches:
 - If..then..else tree comparing values against thresholds

```
if (diffuse < A) diffuse = 0.0;
else if (diffuse < B) diffuse = B;
else if (diffuse < C) diffuse = C;
else diffuse = D;
```

ID textures to map diffuse and specular shading to colors

```
uniform sampler1D diffuseramp;
uniform sampler1D specularramp;
color = e * (texture1D(diffuse, diffuseramp) +
texture1D(specular, specularramp));
```





Toon Shading Demo



http://www.bonzaisoftware.com/npr.html

